



**PASTA ABRASIVA
ULTRAMORDENTE
PLUS A**

GELSON®

AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL DATA SHEET

Rev. 1 dated 21/05/2019

Creamy, ultra-coarse rubbing compound expressly designed for polyurethane clearcoats (cars, trucks, boats) and other automotive and marine coatings, fibreglass surfaces and gel coats.

Silicon-free.

CHARACTERISTICS:

Appearance: creamy paste
Base: O/W aqueous emulsion
Colour: white
Density: 1.25 g/cm³

POLISHING CYCLE:

Machine (polisher) use with foam pad.
On old and/or deeply scratched substrates the product can be applied with merinos wool pads (cod. 8677XX).
Residues' removal and final polishing should be made using a microfiber cloth.



STORAGE:

The product can be stored for 12 months at a temperature not exceeding 25°C when kept in its original package.
Keep away from frost!

Please find available codes and packagings for this product on our corporate website

<http://www.gelson.it/>

The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.